SCHEDULE II

[See rule 3 (1) (17) (ii)]

List of waste constituents with concentration limits

Class A: Based on leachable concentration limits [Toxicity Characteristic Leaching Procedure (TCLP) or Soluble Threshold Limit Concentration (STLC)]

Class	Constituents	Concentration in mg/l
(1)	(2)	(3)
A1	Arsenic	5.0
A2	Barium	100.0
A3	Cadmium	1.0
A4	Chromium and/or Chromium (III) compounds	5.0
A5	Lead	5.0
A6	Manganese	10.0
A7	Mercury	0.2
A8	Selenium	1.0
A9	Silver	5.0
A10	Ammonia	50*
A11	Cyanide	20*
A12	Nitrate (as nitrate-nitrogen)	1000.0
A13	Sulphide (as H ₂ S)	5.0
A14	1,1-Dichloroethylene	0.7
A15	1,2-Dichloroethane	0.5
A16	1,4-Dichlorobenzene	7.5
A17	2,4,5-Trichlorophenol	400.0
A18	2,4,6-Trichlorophenol	2.0
A19	2,4-Dinitrotoluene	0.13
A20	Benzene	0.5
A21	Benzo (a) Pyrene	0.001
A22	Bromodicholromethane	6.0
A23	Bromoform	10.0
A24	Carbon tetrachloride	0.5
A25	Chlorobenzene	100.0
A26	Chloroform	6.0
A27	Cresol (ortho+ meta+ para)	200.0
A28	Dibromochloromethane	10.0
A29	Hexachlorobenzene	0.13
A30	Hexachlorobutadiene	0.5
A31	Hexachloroethane	3.0
A32	Methyl ethyl ketone	200.0
A33	Naphthalene	5.0
A34	Nitrobenzene	2.0
A35	Pentachlorophenol	100.0
A36	Pyridine	5.0
A37	Tetrachloroethylene	0.7
A38	Trichloroethylene	0.5

(1)	(2)	(3)
A39	Vinyl chloride	0.2
A40	2,4,5-TP (Silvex)	1.0
A41	2,4-Dichlorophenoxyacetic acid	10.0
A42	Alachlor	2.0
A43	Alpha HCH	0.001
A44	Atrazine	0.2
A45	Beta HCH	0.004
A46	Butachlor	12.5
A47	Chlordane	0.03
A48	Chlorpyriphos	9.0
A49	Delta HCH	0.004
A50	Endosulfan (alpha+ beta+ sulphate)	0.04
A51	Endrin	0.02
A52	Ethion	0.3
A53	Heptachlor (& its Epoxide)	0.008
A54	Isoproturon	0.9
A55	Lindane	0.4
A56	Malathion	19
A57	Methoxychlor	10
A58	Methyl parathion	0.7
A59	Monocrotophos	0.1
A60	Phorate	0.2
A61	Toxaphene	0.5
A62	Antimony	15
A63	Beryllium	0.75
A64	Chromium (VI)	5.0
A65	Cobalt	80.0
A66	Copper	25.0
A67	Molybdenum	350
A68	Nickel	20.0
A69	Thallium	7.0
A70	Vanadium	24.0
A71	Zinc	250
A72	Fluoride	180.0
A73	Aldrin	0.14
A74	Dichlorodiphenyltrichloroethane (DDT), Dichlorodiphenyldichloroethylene (DDE), Dichlorodiphenyldichloroethane (DDD)	0.1
A75	Dieldrin	0.8
A76	Kepone	2.1
A77	Mirex	2.1
A78	Polychlorinated biphenyls	5.0
A79	Dioxin (2,3,7,8-TCDD)	0.001

Class B: Based on Total Threshold Limit Concentration (TTLC)

Class	Constituent	Concentration in mg/kg
(1)	(2)	(3)
B1	Asbestos	10000
B2	Total Petroleum Hydrocarbons (TPH) (C5 - C36)	5,000

Note:

- (1) The testing method for list of constituents at A1 to A61 in Class-A, shall be based on Toxicity Characteristic Leaching Procedure (TCLP) and for extraction of leachable constituents, USEPA Test Method 1311 shall be used.
- (2) The testing method for list of constituents at A62 to A79 in Class- A, shall be based on Soluble Threshold Limit Concentration (STLC) and Waste Extraction Test (WET) Procedure given in Appendix II of section 66261 of Title 22 of California Code regulation (CCR) shall be used.
- (3) In case of ammonia (A10), cyanide (A11) and chromium VI (A64), extractions shall be conducted using distilled water in place of the leaching media specified in the TCLP/STLC procedures.
- (4) A summary of above specified leaching/extraction procedures is included in manual for characterization and analysis of hazardous waste published by Central Pollution Control Board and in case the method is not covered in the said manual, suitable reference method may be adopted for the measurement.
- (5) In case of asbestos, the specified concentration limits apply only if the substances are in a friable, powdered or finely divided state.
- (6) The hazardous constituents to be analyzed in the waste shall be relevant to the nature of the industry and the materials used in the process.
- (7) Wastes which contain any of the constituents listed below shall be considered as hazardous, provided they exhibit the characteristics listed in Class-C of this Schedule:

1.	Acid Amides
2.	Acid anhydrides
3.	Amines
4.	Anthracene
5.	Aromatic compounds other than those listed in Class A
6.	Bromates, (hypo-bromites)
7.	Chlorates (hypo-chlorites)
8.	Carbonyls
9.	Ferro-silicate and alloys
10.	Halogen- containing compounds which produce acidic vapours on contact with humid air or water e.g. silicon tetrachloride, aluminum chloride, titanium tetrachloride
11.	Halogen- silanes
12.	Halogenated Aliphatic Compounds
13.	Hydrazine (s)

4.4	Transaca.
14.	Hydrides
15.	Inorganic Acids
16.	Inorganic Peroxides
17.	Inorganic Tin Compounds
18.	Iodates
19.	(Iso- and thio-) Cyanates
20.	Manganese-silicate
21.	Mercaptans
22.	Metal Carbonyls
23.	Metal hydrogen sulphates
24.	Nitrides
25.	Nitriles
26.	Organic azo and azooxy Compounds
27.	Organic Peroxides
28.	Organic Oxygen Compounds
29.	Organic Sulphur Compounds
30.	Organo- Tin Compounds
31.	Organo nitro- and nitroso compounds
32.	Oxides and hydroxides except those of hydrogen, carbon, silicon, iron, aluminum, titanium, manganese, magnesium, calcium
33.	Phenanthrene
34.	Phenolic Compounds
35.	Phosphate compounds except phosphates of aluminum,
	calcium and iron
36.	Salts of pre-acids
37.	Total Sulphur
38.	Tungsten Compounds
39.	Tellurium and tellurium compounds
40.	White and Red Phosphorus
41.	2-Acetylaminofluorene
42.	4-Aminodiphenyl
43.	Benzidine and its salts
44.	Bis (Chloromethyl) ether
45.	Methyl chloromethyl ether
46.	1,2-Dibromo-3-chloropropane
47.	3,3'-Dichlorobenzidine and its salts
48.	4-Dimethylaminoazobenzene
49.	4-Nitrobiphenyl
50.	Beta-Propiolactone

CLASS C: Based on hazardous Characteristics

Apart from the concentration limit given above, the substances or wastes shall be classified as hazardous waste if it exhibits any of the following characteristics due to the presence of any hazardous constituents:

Class C1: Flammable- A waste exhibits the characteristic of flammability or ignitability if a representative sample of the waste has any of the following properties, namely:-

- (i) flammable liquids, or mixture of liquids, or liquids containing solids in solution or suspension (for example, paints, varnishes, lacquers, etc; but not including substances or wastes otherwise classified on account of their dangerous characteristics), which give off a flammable vapour at temperature less than 60°C. This flash point shall be measured as per ASTM D 93-79 closed-cup test method or as determined by an equivalent test method published by Central Pollution Control Board;
- (ii) it is not a liquid and is capable, under standard temperature and pressure, of causing fire through friction, absorption of moisture or spontaneous chemical changes and, when ignited, burns vigorously and persistently creating a hazard;
- (iii) it is an ignitable compressed gas;
- (iv) It is an oxidizer and for the purposes of characterisation is a substance such as a chlorate, permanganate, inorganic peroxide, or a nitrate, that yields oxygen readily to stimulate the combustion of organic matter.

Class C2: Corrosive- A waste exhibits the characteristic of corrosivity if a representative sample of the waste has either of the following properties, namely:-

- (i) it is aqueous and has a pH less than or equal to 2 or greater than or equal to 12.5;
- (ii) it is a liquid and corrodes steel (SAE 1020) at a rate greater than 6.35 mm per year at a test temperature of 55 °C;
- (iii) it is not aqueous and, when mixed with an equivalent weight of water, produces a solution having a pH less than or equal to 2 or greater than or equal to 12.5;
- (iv) it is not a liquid and, when mixed with an equivalent weight of water, produces a liquid that corrodes steel (SAE1020) at a rate greater than 6.35 mm per year at a test temperature of 55 °C. Note:

For the purpose of determining the corrosivity, the Bureau of Indian Standard 9040 C method for pH determination, NACE TM 01 69: Laboratory Corrosion Testing of Metals and EPA 1110A method for corrosivity towards steel (SAE1020) to establish the corrosivity characteristics shall be adopted.

Class C3: Reactive or explosive- A waste exhibits the characteristic of reactivity if a representative sample of the waste it has any of the following properties, namely:-

- it is normally unstable and readily undergoes violent change without detonating;
- (ii) it reacts violently with water or forms potentially explosive mixtures with water;
- (iii) when mixed with water, it generates toxic gases, vapours or fumes in a quantity sufficient to present a danger to human health or the environment;
- (iv) it is a cyanide or sulphide bearing waste which, when exposed to pH conditions between 2 and 12.5, can generate toxic gases, vapours or fumes in a quantity sufficient to present a danger to human health or the environmental;
- it is capable of detonation or explosive reaction if it is subjected to a strong initiating source or if heated under confinement;
- (vi) it is readily capable of detonation or explosive decomposition or reaction at standard temperature and pressure;
- (vii) it is a forbidden explosive.

Class C4: Toxic- A waste exhibits the characteristic of toxicity, if, :-

- (i) the concentration of the waste constituents listed in Class A and B (of this schedule) are equal to or more than the permissible limits prescribed therein;
- (ii) it has an acute oral LD50 less than 2,500 milligrams per kilogram;
- (iii) it has an acute dermal LD50 less than 4,300 milligrams per kilogram;
- (iv) it has an acute inhalation LC50 less than 10,000 parts per million as a gas or vapour;
- (v) it has acute aquatic toxicity with 50% mortality within 96 hours for zebra fish (*Brachidanio rerio*) at a concentration of 500 milligrams per litre in dilution water and test conditions as specified in BIS test method 6582 2001.
- (vi) it has been shown through experience or by any standard reference test- method to pose a hazard to human health or environment because of its carcinogenicity, mutagenecity, endocrine disruptivity, acute toxicity, chronic toxicity, bio-accumulative properties or persistence in the environment.
- Class C5: Substances or Wastes liable to spontaneous combustion Substances or Wastes which are liable to spontaneous heating under normal conditions encountered in transport, or to heating up on contact with air, and being then liable to catch fire.
- Class C6: Substances or Wastes which, in contact with water emit flammable gases-Substances or Wastes which, by interaction with water, are liable to become spontaneously flammable or to give off flammable gases in dangerous quantities.
- **Class C5: Oxidizing -** Substances or Wastes which, while in themselves not necessarily combustible, may, generally by yielding oxygen cause, or contribute to, the combustion of other materials.
- **Class C8: Organic Peroxides -** Organic substances or Wastes which contain the bivalent O-O structure, which may undergo exothermic self-accelerating decomposition.
- Class C9: Poisons (acute) Substances or Wastes liable either to cause death or serious injury or to harm human health if swallowed or inhaled or by skin contact.
- **Class C10: Infectious substances -** Substances or Wastes containing viable micro-organisms or their toxins which are known or suspected to cause disease in animals or humans.
- Class C11: Liberation of toxic gases in contact with air or water Substances or Wastes which, by interaction with air or water, are liable to give off toxic gases in dangerous quantities.
- Class C12: Eco-toxic- Substances or Wastes which if released, present or may present immediate or delayed adverse impacts to the environment by means of bioaccumulation or toxic effects upon biotic systems or both.
- **Class C13: Capable,** by any means, after disposal, of yielding another material, e.g., leachate, which possesses any of the characteristics listed above.