EXECUTIVE SUMMARY

DRAFT ENVIRONMENTAL IMPACT ASSESSMENT REPORT OF ROUGH STONE & GRAVEL QUARRY

(As per EIA Notification, 2006 dated 14.09.2006 and its amendments)

Category: B1 (Cluster)

AREA DETAILS

Extent : 3.28.0 Ha

S. F. Nos.: 272/2A, 2B, 2C and 2D

Village : Chettikurichi

Taluk : Kayathar

District: Thoothukkudi

PROJECT PROPONENT

THIRU. S.KANDASAMY

S/o Shanmugam No.102, Anna new street, Kalugumalai Taluk, Thoothukudi District, Tamil Nadu.

EIA CONSULTANT

AADHI BOOMI MINING & ENVIRO TECH (P) LTD (QCI/NABET Accredited EIA Organization)

3/216, K.S.V Nagar, Narasothipatti, Alagapuram (PO),

Salem – 636004, Website: <u>www.abmenvirotec.com</u>

Email: <u>abmenvirotech@gmail.com</u>, <u>suriyakumarsemban@gmail.com</u>

Mob: 9842729655, 9443290855.

Proponent: Thiru S.Kandasamy, Rough Stone and Gravel quarry, Thoothukudi District

Executive Summary

1.0 INTRODUCTION

Thiru. S.Kandasamy S/o. Shanmugam, residing at No. 120, Anna New Street, Kalugumalai Taluk, Thoothukudi District, Tamil Nadu has applied for grant of permission for quarrying Rough Stone & Gravel over an Extent of 3.28.0 Ha located in S.F. No. 272/2A, 2B, 2C and 2D, Chettikurichi Village, Kayathar Taluk, Thoothukkudi District, Tamil Nadu for the period of five years.

Based on his application, the Assistant Director, Dept of Geology and Mining, Thoothukudi District has directed the applicant, Thiru.S.Kandasamy vide his precise area communication letter Roc No. G.M.1/861/2022 dated 14.07.2023 to get approved mining plan and obtain Environmental clearance for grant of Rough Stone & Gravel quarry lease.

The mining plan was approved by Assistant Director, Department of Geology and Mining, Thoothukudi vide letter Roc No. G.M.1/861/2022 dated 01.09.2023.

As per the Environmental Impact Assessment (EIA) Notification dated 14th September 2006 and its amendments, the proposed project falls under 1(a) Mining of minerals, Category – B1(Cluster) in view of project's cluster area >5 and <250 Ha. So, this project has to obtain Terms of Reference for conducting EIA studies. Therefore, the applicant applied for ToR through PARIVESH Portal vide online proposal no. SIA/TN/MIN/447362/2023 Dated 07.10.2023. The ToR proposal was appraised in the 443rd SEAC meeting held on 08.02.2024. After detailed discussions, the Authority accepts the recommendation of SEAC and granted Terms of Reference (ToR) along with Public Hearing vide TOR Identification No. TO23B0108TN5752566N.

1.1 SCOPE OF THEPROJECT

The scope of the project is to operate rough stone and gravel quarry after conducting public hearing through TNPCB, Thoothukudi and obtaining environmental clearance from SEIAA/SEAC, Tamil Nadu. The proposed quarry will be operated by adopting environmental management plan prepared by EIA consultant and with compliance of conditions given by SEIAA/SEAC and TNPCB.

Proponent: Thiru S.Kandasamy, Rough Stone and Gravel quarry, Thoothukudi District

1.2 PROJECT DESCRIPTION

Table 1.1 Project Details

| Project Details | | | | | | | | |
|-----------------------|---|--------------------------|----------------|------------------|--|--|--|--|
| Proponent | Thiru. S.Kandasam | y S/o. Shanm | ugam | | | | | |
| Total Mine Lease Area | 3.28.0 Ha (Patta Land) | | | | | | | |
| Survey No. | 272/2A, 2B, 2C and 2E | 272/2A, 2B, 2C and 2D | | | | | | |
| Site Location | Chettikurichi Villago Tamil Nadu | e, Kayathar [·] | Taluk, Thoothu | ıkkudi District, | | | | |
| Geographical | Latitude: 9°3'50.79 | 9"N to 9°3'59. | 90"N | | | | | |
| Co-ordinates | Longitude: 77°43'51 | .47"E to 77°4 | 3'56.63" E | | | | | |
| Toposheet No. | 58 G/12 | | | | | | | |
| Elevation | Elevation of the area | a is 114m abo | ve MSL | | | | | |
| | Accessi | bility | | | | | | |
| Nearest Habitation | Temporary shed of | crusher unit - | 260m - SW | | | | | |
| Nearest Villages | Chettikurichi – 1.3kr | n - SE | | | | | | |
| Nearest Settlement | Name of Village | Direction | Distance | Population | | | | |
| | Chettikurichi | SE | 1.6 km | 3420 | | | | |
| | Cithamparampatti | NE | 2.8 km | 1421 | | | | |
| | Kattarankulam | NE | 4.6 km | 1850 | | | | |
| | Vellalankottai | SE | 4.5 km | 1819 | | | | |
| Nearest Town | Kalugumalai – 9.4kn | n – NW | | | | | | |
| | Kayathar – 14km - S | E | | | | | | |
| Nearest Roadway | NH 44 – 7.1km – E (Kashmir to Kanyakumari) SH 76– 8.6km - N (Nallatinputhur to Puliyangudi) MDR 160m – 860m – E (Kayathar to Kalugumalai) Village road – 1.6km – E (Chettikurichi to Gopalapuram) Approach road is available near to this project site. | | | | | | | |
| Nearest Railway | Kumarapuram Railw | | | | | | | |
| station | Kadambur Railway S | Station – 16kr | n – SE | | | | | |
| Nearest Airport | Thoothukudi Airpor | t–50km – SE | | | | | | |
| | Environmental | Sensitivenes | S | | | | | |
| Interstate Boundary | There is no interstate boundary within 15km radius. Tamil Nadu – Kerala Interstate boundary is located 52 km away from lease area in west direction. | | | | | | | |
| Coastal Zone | Bay of Bengal – 53k | m - SE. | | | | | | |
| Reserve Forest | The project land is not a forest land, it is patta land. There is no Reserve Forest and Protected Forest found within 10km radius. Kurumalai R.F – 13km – E | | | | | | | |

| | Uthumalai R.F – 17km -SW | | | | | | | | |
|---------------------------|---|---|-------------------------|--------------|--|--|--|--|--|
| | The proposed project site does not attract Forest | | | | | | | | |
| | Conserv | ation Act, 1980. | | | | | | | |
| Wildlife sanctuary | Nil withi | Nil within 10km radius. | | | | | | | |
| - | Gangaikondan Spotted Deer Sanctuary – 26km – S. It is | | | | | | | | |
| | notified | notified Sanctuary by MOEF&CC vide S.O.2773 (E) dated | | | | | | | |
| | 31/07/2 | 019. | | | | | | | |
| | The Pro | oposed project site does no | ot attract t | the Wildlife | | | | | |
| | (Protecti | ion) Act, 1972. | | | | | | | |
| Water bodies | S.No | Water body name | Distance | Direction | | | | | |
| | 1 | A small lake | 740m | N | | | | | |
| | 2 | Nalanthula lake | 1.3km | NNW | | | | | |
| | 3 | Mel Nalanthula lake | 1.8km | NNW | | | | | |
| | 4 | North Konarkottai lake I | 988m | SW | | | | | |
| | 5 | North Konarkottai lake II | 1.5km | S | | | | | |
| | 6 | Uppodai River | 2.0km | E | | | | | |
| | 7 | Water body with weir across | 1.9km | ENE | | | | | |
| | / River Uppodai | | | | | | | | |
| | 8 | A odai | 2.0km | SW | | | | | |
| | 9 | Olaikulam lake I | 2.7km | SSW | | | | | |
| | 10 | Olaikulam lake II | 2.9km | SSW | | | | | |
| | 11 | Vellappaneri lake | 3.8km | SW | | | | | |
| | 12 | Karisalkulam lake | 3.6km | NW | | | | | |
| | 13 | A odai | 4.7km | NE | | | | | |
| | 14 | Water body with weir across 4.7km NE | | | | | | | |
| | | Odai | 1,7 1(11) | | | | | | |
| Defense Installations | Nil withi | n 10km radius | | | | | | | |
| Critically Polluted area | Nil withi | n 10km radius | | | | | | | |
| Quarries around 500m | Three ex | kisting quarries and one prese | nt proposed | d quarry are | | | | | |
| radius | located | within the 500m radius from th | e lease bou | ndary of the | | | | | |
| (AD Letter furnished) | propose | ed project site. | | | | | | | |
| | Total Clu | uster area: 9.56.7 Ha | | | | | | | |
| | AD Clus | ter Letter: Roc No.G.M.1/861/20 | 022, dated 0 | 1.09.2023 | | | | | |
| Seismic zone | Zone-II, | Low damage risk zone as per B | MTPC, Vulne | erability | | | | | |
| | atlas Sei | smic zone of India IS: 1893-200 | 2 | - | | | | | |
| | • | Mining Details | | | | | | | |
| Method of Mining | Open ca | st Mechanized method of mini | ng | | | | | | |
| Geological resources | 9,78,90 | Om³ | | | | | | | |
| - | 5,10,300 | Om ³ of Rough Stone & 1,08,6 | 516m ³ of To | op soil and | | | | | |
| Mineable reserves Gravel | | | | | | | | | |
| Glavei | | | | | | | | | |

| Production (95%) | Rough stone – 3,01,678m³ for five years or 60,336m³ per annum (Avg) Top soil & Gravel – 80,448m³ for three years or 26,816m³ per annum | | | |
|---|---|--|--|--|
| Reject (5%) | 15878 m ³ | | | |
| Top soil | Top soil & Gravel – 80,448m ³ | | | |
| Ore: Waste ratio | 1: 0.05 | | | |
| Depth of Mining | 34m bgl (Ultimate Depth) 0-4m - Top soil & Gravel 4-34m – Rough stone | | | |
| Water Table | 55-60m bgl | | | |
| Road design 1: 10 inside the pit and ramp 1:16 for transport | | | | |
| Overall Pit Slope | 45° | | | |
| Period of Lease 5 Years from the date of execution | | | | |
| Project Cost Rs. 81 Lakhs | | | | |
| EMP Cost | Rs. 6.75 Lakhs | | | |
| CER Cost | Rs.5.0 Lakhs | | | |




Fig No 1.1 Toposheet showing location of proposed rough stone quarry with 10km radius study area




Fig No 1.2 Google earth image showing location and route for proposed rough stone and gravel quarry




Fig No 1.3 Conceptual mining plan




Fig No 1.4 Combined sketch

Proponent: Thiru S.Kandasamy, Rough Stone and Gravel quarry, Thoothukudi District

1.3 Description of the environment

1.3.1 Base line environmental study

Collection of base line data is an integral part of the preparation of environmental impact assessment reports. The baseline monitoring study has been carried out during December 1st 2022 – February 28th, 2023 to assess the existing environmental scenario in the area. For the purpose of EIA studies, mine lease area was considered as the core zone and area outside the mine lease boundary up to 10km radius from the lease boundary was considered as buffer zone.

Table No 1.2 Baseline Data

| Particulars | Details | Standards | | | | | | |
|---|----------------------------------|------------------------|--|--|--|--|--|--|
| Meteorology (December 1st 2022 – February 28th, 2023) | | | | | | | | |
| Rainfall (Avg.) | 211.47 mm (study period) | | | | | | | |
| Temperature (Avg.) | 26°C | | | | | | | |
| Wind speed (Avg.) | 5.2 m/s | | | | | | | |
| Wind Direction | Predominantly from N, NW, NE | | | | | | | |
| | Ambient Air Quality (NAAQ | S) | | | | | | |
| PM ₁₀ | 39-54 μg/m ³ | 100 μg/m ³ | | | | | | |
| PM _{2.5} | 15-36 μg/m ³ | 60 μg/m ³ | | | | | | |
| SO ₂ | 9-19 µg/m³ | 80 μg/m ³ | | | | | | |
| NO _x | 11-30 μg /m³ | 80 μg/m ³ | | | | | | |
| | Noise Level (CPCB Standard | s) | | | | | | |
| | | Industrial Area | | | | | | |
| Day time | Core zone – 39.9 – 47.2 dB (A) | Day Time - 75 dB (A) | | | | | | |
| (6:00 am - 10:00 pm) | Buffer zone – 39.5 – 45.1 dB (A) | Residential Area | | | | | | |
| | | Day Time – 55 dB (A) | | | | | | |
| | | Industrial Area | | | | | | |
| Night time | Core zone – 32.4– 39.5 dB (A) | Night Time – 70 dB(A) | | | | | | |
| (10:00pm - 06:00 am) | Buffer zone – 31.8 – 39.7 dB(A) | Residential Area | | | | | | |
| | | Night Time – 45 dB (A) | | | | | | |
| Wate | er Quality IS 10500:2012 (Desira | ble limits) | | | | | | |
| рН | 7.15 – 7.89 | 6.5 to 8.5 | | | | | | |
| TDS | 700 - 1064 mg/l | 500 mg/l | | | | | | |
| Electrical conductivity at 25°C | 1198 - 1720 micromhos/cm | - | | | | | | |
| Total Hardness as CaCO ₃ | 200 - 423 mg/l | 200 mg/l | | | | | | |

⁹ | P a g e **Consultant:** Aadhi Boomi Mining & Enviro Tech (P) Ltd, Salem, Tamil Nadu

| Total suspended solids | 1 - 2 | IS:3025:P.16:1984:R.2012 | | | | |
|--------------------------|----------------|---|--|--|--|--|
| Chlorides Cl | 222 – 430 mg/l | 250mg/l | | | | |
| Total iron Fe | 0.03-0.08 mg/l | 0.3mg/l | | | | |
| Sulfates SO ₄ | 16-90 mg/l | 200 mg/l | | | | |
| | Soil Quality | | | | | |
| рН | 7.12 – 8.2 | Neutral to slightly alkaline | | | | |
| Bulk density | 1.02-1.22 g/cc | Favorable physical condition for plant growth | | | | |
| Hydro Geology | | | | | | |
| Depth of Mining | 34m bgl | | | | | |
| Water Table | 55-60m bgl | | | | | |

1.4 ANTICIPATED ENVIRONMENTAL IMPACTS AND MITIGATION MEASURES

1.4.1 Air Environment

The air borne particulate matter is the main air pollutant by opencast mining. The mining operation will be carried out by adopting mechanized methods which involves Jack Hammer drilling and blasting, excavation, loading and transportation.

AERMOD - Model was used for prediction of impact of PM_{10} during conditions i) Loading/unloading and transportation of rough stone and weathered rock by trucks on Haul roads ii) During blasting of minerals. Total predicted 24-h maximum GLC of PM_{10} at project site for scenario 1 i.e loading-unloading and transportation and scenario 2 i.e blasting was $67.08\mu g/m^3$ and $56.23~\mu g/m^3$ respectively occurred at the project site after superposition of base-line value $49~\mu g/m^3$ over the incremental $18.08~\mu g/m^3$ and $7.23~\mu g/m^3$ respectively due to combined impact of loading and unloading and transportation over the haul road and due to blasting.

The predicted incremental GLC of SO_x and NO_x for scenario 3 i.e. due to the operation of excavator and movement of vehicle in the project site were found to be BDL $\mu g/m^3$. The total GLC during mining activity was found within the prescribed limit of NAAQS. The mitigation measures for controlling air pollution due to proposed quarry are given in Table No 1.3.

1.4.2 Noise Environment

Noise pollution poses a major health risk to the mine workers. The sources of noise in the open cast proposed rough stone and gravel quarry are such as Drilling, Blasting, and during movement of vehicles.

The noise generated by the mining activity is dissipated within the core zone. This is

Proponent: Thiru S.Kandasamy, Rough Stone and Gravel quarry, Thoothukudi District

because of distance involved and other topographical features adding to the noise attenuation. From the results, it can be seen that the ambient noise levels (day time and night time) at all the locations remain within permissible limits prescribed by CPCB and 90dB (A) norms of DGMS. At present there is no mining activity carried out. However, the expected noise levels are not likely to have any effect. Precaution will be made to keep down the noise exposure level of 85 dB (A) to the operating personnel for 8 hrs duration. The charge per blast of 75kg is below the Peak Particle Velocity of 5mm/s for the habitation located at the distance of 1300m. So, ground vibrations due to blasting activities will not cause any impact to the nearest habitations.

The mitigation measures for controlling noise pollution due to proposed mining activity are given in Table No 1.3.

1.4.3 Water Environment

1.4.3.1 Ground Water

Mining operations can affect groundwater quality in several ways. The most obvious occurs in the mining below the water table, either in underground workings or open pits. This provides a direct conduit to aquifers. Groundwater quality is also affected when waters (natural or process waters or wastewater) infiltrate through surface materials (including overlying waste or other material) into ground water.

The impact due to proposed mining activity on the water quality is expected to be insignificant because of no use of chemicals or hazardous substances during mining process. The mining activity will not intersect ground water table as the depth of mining is 34m bgl whereas the depth of ground water table is identified as 55-60m bgl.

The ground water samples were collected at 5 locations to identify the present water quality status. TDS from all the water samples exceeds the acceptable limits of 500mg/l and TH in the water sample of Chettikurichi village only was found within the acceptable limit of 200mg/l. The chloride also exceeds the acceptable limits of 250mg/l in all the samples except from Chettikurichi and Ramiyampatti Village. Based on the Water Quality Index calculated, water quality from Chettikurichi and Ramiyampatti Village is found good and water quality from all other locations are found poor. For excellent water quality, the ground water from all the location required to be treated by reverse osmosis to reduce dissolved solids and total hardness to the required rate. As the water quality of Chettikurichi village is good, the reject during the R.O treatment of water will be very less.

Proponent: Thiru S.Kandasamy, Rough Stone and Gravel quarry, Thoothukudi District

1.4.3.2 Surface Water

Since major water bodies are located beyond 1km radius of the project site, the possibility of affecting water quality in those water bodies due to proposed mining activity is less.

1.4.4 Soil Environment

For the five-year plan period, the generation of top soil and gravel is estimated as 80,448m³ upto the depth of 4m from the surface. From this quantity, the generated top soil will be dumped along 7.5m inner boundary of the lease area and generated gravel generated will be sold to the local needy customers. The top soil will be used to develop greenbelt within the lease area.

The management of top soil is given in Table No 1.3.

1.4.5 Waste Dump

The proposed rate of production of rough stone for five years is about 3,10,678m³ at the rate of 95% recovery up to permissible depth. The 5% reject of 15878m³ will be dumped within the mining lease area (south side) as per approved mining plan. All rejects dumped will be backfilled at the end of mine life. The management of reject/waste dump is mentioned in Table No 1.3.

1.4.6 Biological Environment

There is no Reserve Forest or any Protected Forest located within 10km radius of the project site and there are no notified endangered species in the area, which may be affected due to the mining activities; therefore, the biological environment will not have significant impact due to mining activity. The impact on the biological environment due to amount of dust generation is minimized by well-developed green belt in and around mining lease area.

1.4.7 Land Environment

Rough stone & gravel quarry project will result in disturbance of the land use pattern of the mine lease area. The land degradation is unavoidable during mining activities like excavation, overburden dumping, soil extraction etc. So, reclamation of mined out land and proper formation of benches will be given due importance.

The land use analyses show that the tree plantation is found on the west side of the lease area and existing rough stone quarries are found on north and south side. Minor agricultural activity is carried out within 500m radius in northeast and

Proponent: Thiru S.Kandasamy, Rough Stone and Gravel quarry, Thoothukudi District

southeast side. The dumping of rejects and dust deposition in the adjacent lands may affect the land use around the site.

At the end of the project, the quarried-out pit will be act as water storage pond. The stored water will be used for developing agricultural activity around the mining lease area. It will improve the livelihood of village people.

The mitigation measure for land degradation is mentioned in Table No 1.3.

1.4.8 Socio Economic Environment

The quarrying activity will definitely increase the employment opportunity (directly as well as indirectly) in the project area. Some of these impacts would be beneficial. The expectation of the people of area is concerned towards employment, education, road and health facilities. The literacy rate may be increased with the economic benefits which may arise from the quarrying activities.

Direct Employment - 21 persons

Indirect Employment - 40 persons

Indirect employment is that people will keep shops such as tea shops, hotels, spare parts store, mechanic shed, etc. around the quarry depending on the proposed projects. Population rate is increased day by day in India. It is necessary to create employment to all people for their livelihood and country's economic development.

Table 1.3 Environmental Management Plan

| S.No | Parameters | Mining Activity | Mitigation measures |
|------|-----------------|------------------|---|
| 1 | Air Environment | Drilling | Dust extractor or wet drilling to be followed to control dust at |
| | | | source of emission |
| | | | Use of Sharp drill bits for drilling holes and charging the holes |
| | | | by using optimum charge and using time delay detonator |
| | | Blasting | o Regular water sprinkling on blasted heaps at regular intervals |
| | | | will help in reducing considerable dust pollution |
| | | Loading | Water sprinkling be done before loading by making it moist |
| | | Transportation | o Water sprinklers along the sides of haul road shall be fixed to |
| | | | control fly of dust while transporting minerals and waste |
| | | | Overloading will be prevented |
| | | | Trucks/Dumpers covered by tarpaulin covers |
| | | DG Sets | DG sets will be used only during power failure |
| | | | Adequate stack height for DG sets will be provided as per CPCB |
| | | | norms |
| | | General measures | Avenue trees along roads around ML boundary shall be planted |
| | | | as per the norms of MoEF to control fly of dust. |
| | | | o Labours engaged in such dust prone areas should be provided |
| | | | with safety devices like ear muff, mask, goggles as per the MMR, |
| | | | 1961 amendments and circulars of DGMS. |
| | | | Regular health check-up of workers and nearby villagers in the |
| | | | impacted area should be carried out and also regular |
| | | | occupational health assessment of employees should be carried |

| | | | out as per the Factories Act | |
|---|-------------|------------------|---|-------------------|
| | | | o Ambient Air Quality Monitoring will be condu | cted on regular |
| | | | basis to assess the quality of ambient air. | |
| 2 | Water | Surface water | o Wastewater discharge from mine will be treated | in settling tanks |
| | Environment | | before using for dust suppression and tree plant | ation purposes. |
| | | Ground water | o The mining activity will not intersect the ground | water table |
| | | | \circ Desilting will be carried out before and imme | diately after the |
| | | | monsoon season | |
| | | Storm water | Pit will be used for Storage of rainwater | |
| | | | \circ Rain water will be collected in sump in the minir | g pit and will be |
| | | | allowed to store and pumped out to surface se | etting tank of 15 |
| | | | m x 10m x 3m to remove suspended solids if ar | y. This collected |
| | | | water will be judiciously used for dust suppressi | on onwards and |
| | | | such sites where dust likely to be generated and | d for developing |
| | | | green belt. | |
| | | | $\circ\hspace{0.4cm}$ The proponent will collect and judicially utilize | the rainwater as |
| | | | part of rain water harvesting | |
| | | General measures | o Regular monitoring and analyzing the quality of | water |
| 3 | Noise | Drilling | o Limiting time exposure of workers to excessive r | oise |
| | Environment | Blasting | o Carrying out blasting only during day time and | d not on cloudy |
| | | | days | |
| | | | \circ Noise levels will be controlled by using opt | imum explosive |
| | | | charge, proper delay detonators and prope | r stemming to |
| | | | prevent blow out of holes. | |

| | | | Providing proper noise proof enclosure for the worke separated from the noise source and noise prone equipment |
|---|-----------|------------------|---|
| | | Transportation | Proper and regular maintenance of vehicles, machinery are other equipments. The noise generated by the machinery will be reduced to proper lubrication of the machinery and other equipments. Speed of trucks entering or leaving the mine will be limited to moderate speed to prevent undue noise from empty vehicles. Adequate silencers will be provided in all the diesel engines of vehicles. Minimum use of horns and speed limit of 10 km/hr in the village area. It will be ensured that all transportation vehicles carry a value. |
| | | General measures | PUC Certificates Use of personal protective devices i.e., earmuffs and earplugs to workers, who are working in high noise generating areas Provision of Quiet areas, where employees can get relief from workplace noise. The development of green belts around the periphery of the mine to attenuate noise. Regular medical check—up and proper training to personnel to create awareness about adverse noise level effects. |
| 4 | Vibration | Blasting | Specific charge pattern has to be designed by proper tri vibration studies with varying charge ratios. |

| | | | Milli second detonators shall be used preferably 25–50ms per delay to control vibrations If the vibration still exceeds the limit a long Trench to a depth of 6m may cut in the direction of wave's movement to break longitudinal waves which travel close to surface, preferably near |
|---|---------------------|---------------------------|--|
| | | | mine buffer zone o In spite of all measures periodical testing of vibration and noise using approved seismograph by DGMS has to be followed as a part of Environmental monitoring |
| 5 | Soil Environment | Topsoil | Humus top soil shall be preserved for reuse in afforestation and agriculture Top soil should not be mixed with other waste or reject materials. It should be conserved by judicious utilization in the mine premises Garland drains will be provided around the mine and dumps to arrest any soil from the mine area being carried away by the rain water. This will also avoid the soil erosion and siltation in the mining pits and maintaining the stability of the benches |
| 6 | Waste Dump | Stabilization of Dumps | The rejects\ waste dump shall be properly terraced in to 1.5m benches with proper repose angle and then the top soil shall be spread over the dumps and slope to make them humus for some time, after the soil suitable for water retention trees will be planted at the top, slope and toe of the stabilized dumps to form vegetation |

| | | | 0 | Garland drainage around dump shall prevent under wash of |
|---|---------------------|-------------|-------|--|
| | | | O | dump by hydrostatic pressure to be developed by surface water |
| | | | | and control wash outs and collapse |
| 7 | Plantation | ease and | 0 0 0 | Provision of green belt all along the periphery of the lease area for control of dust and to attenuate noise Stabilization of Dump with plantation It is strongly recommended that the loss of plant in each year will be counted and again planted in subsequent plantation. The plant should be planted taken from nursery, where the survival rate is high. |
| 8 | Land Environment | | 0 0 0 | The restoration of the degraded land would cover backfilling and terracing with the overburden / wastes and surfacing the same with top soil. Provision of Garland drainage around the dumps Fast growing trees and other native shrubs would be planted to stabilize the reclaimed land Appropriate measures will be taken for green belt development. The rain water will be stored in the pit which will recharge the ground water as a part of rain water harvesting scheme for irrigating the nearby agricultural lands. |
| 9 | Socio Economic | | 0 | Good maintenance practices will be adopted for machinery and equipment, which will help to avert potential noise problems. Green belt will be developed in and around the project site as per Central Pollution Control Board (CPCB) guidelines. |

Proponent: Thiru S.Kandasamy, Rough Stone and Gravel quarry, Thoothukudi District

| | | Drilling, blasting etc at specified location will be followed with proper schedule. Appropriate air pollution control measure will be taken so as to minimize the environmental impact within the core zone. An emergency preparedness plan will be prepared in advance to deal with firefighting, evacuation and local communication. For the safety of workers, personal protective appliances like hand gloves, helmets, safety shoes, goggles, aprons, nose mask and ear protecting devices has been provided which meet 'BIS (Bureau of Indian Standards). As a part of CSR activities community welfare measures will be taken by Proponent through local Panchayat |
|----|------------------------|---|
| 10 | Occupational Health | First-aid facilities as per provisions under Rule (44) of Mines Rules 1955 Initial and Periodical medical examination shall be conducted for the employees under Rule 29B & 45 (A). Insurance will be taken in the name of the labourers working in the mines Workers involved in mining work shall be provided protective equipments such as Thick Gloves, Goggles, ear plugs, safety boot wears, etc |

1.5 Analysis of Alternatives

The quarrying site is dependent on the geology and mineral deposition of the area. Hence, this project is, mineral and site specific and no alternative site considered for this project.

1.6 Environmental Monitoring Program

Success of any environmental management programme depends upon the efficiency of the organizational set up responsible for the implementation of the programme. Regular monitoring of the various environmental parameters is also necessary to evaluate the effectiveness of the management programme. Environmental Monitoring Programme will be conducted for various environmental components as per conditions stipulated in the Environmental Clearance Letter issued by SEIAA & Consent to Operate issued by TNPCB.

Table No: 1.4 Post Project Environmental Monitoring Program

| S. | Environment | Location | Mon | itoring | Remarks |
|-----|--|------------------------|----------|-------------|-------------------|
| No. | Attributes | | Duration | Frequency | |
| 1 | Meteorology | Continuous | 24 hours | Monthly | Wind speed, |
| | and Air Quality | monitoring weather | | Once | direction, |
| | | station in core zone/ | | | Temperature, |
| | | nearest IMD station | | | Relative humidity |
| | | | | | and Rainfall. |
| 2 | Air Pollution | 5 locations (One | 8 hours | Once in six | Fine Dust Sampler |
| | Monitoring – | station in the core | | months | and Respirable |
| | PM _{2.5} , PM ₁₀ , | zone and at least | | | Dust Sampler |
| | SO ₂ and NO _x | one in nearby | | | |
| | | residential, area, one | | | |
| | | in the upwind, two | | | |
| | | station on the | | | |
| | | downwind direction | | | |
| | | and one in cross | | | |
| | | wind direction). | | | |
| 3 | Water Pollution | Mine effluents, Set | _ | Once in six | Phyiso–chemical, |
| | Monitoring | of grab samples | | months | microbiological |
| | | during pre and post | | | characteristics |
| | | monsoon for | | | |
| | | ground and surface | | | |
| | | water in the vicinity. | | | |
| 4 | Hydrogeology | Water level in open | - | Once in six | Water level |
| | | wells in buffer zone | | months | monitoring |
| | | around 1km at | | | devices may be |
| | | specific wells | | | used. |

| 5 | Noise | Mine | Boundary, | 24 hours | Monthly | Sound level meter |
|---|-----------|------------------|-------------|----------|-------------|-------------------|
| | | high | noise | | Once | |
| | | generating areas | | | | |
| | | within the | e lease and | | | |
| | | at the | nearest | | | |
| | | residentia | l area | | | |
| 6 | Vibration | At the | nearest | _ | During | Digital |
| | | habitation | n (in case | | blasting | Seismograph |
| | | of reporti | ng) | | operation | |
| 7 | Soil | Core Z | one and | _ | Once in six | Physical and |
| | | Buffer zo | one (Grab | | months | Chemical |
| | | samples) | | | | characteristics |

1.7 Project Benefits


The proponent, **Thiru. S.Kandasmy** is very much conscious of his obligations to society at large. Under plantation programme, it is suggested to develop green belt further all along the boundary of the quarry lease area. Apart from the green belts and aesthetic plantation for eliminating fugitive emissions and noise control, all other massive plantation efforts will be executed with the assistance of experts and cooperation of the local community.

The mining activity will create rural employment. In addition, there will be indirect employment to many more people in the form of contractual jobs like construction of infrastructural facilities, transportation to destinations, sanitation, supply of goods and services to the mine and other community services, etc···The local population will have preference to get an employment. Part of the royalty is given to local bodies by the State Govt. for the welfare and development of the village. The proponent helps in socio economic development of the village by providing education facilities to children's, procuring sports equipments, welfare amenities like drinking water to school, road facilities to villages and employment opportunities to nearby villagers. CSR budget is allocated as 2.5% of the profit.

1.8 Environmental Management Cell (EMC)

It is important to have a permanent organizational set up for implementation of environmental management plan. Conscious of this, the project proponent creates Environmental Management Cell.

Environmental Management Cell (EMC) will be headed by Mines Manager supported by adequate number of personnel and third party (Environment Consultant) having sufficient educational and professional qualification and experience to discharge responsibilities related to environmental management including statutory compliance, pollution prevention, environmental monitoring, maintenance of pollution control equipment and green belt development as well as maintenance.



1.5 Chart of Environment Management Cell

1.9 Environmental Policy of the Thiru S.Kandasamy, Rough Stone and Gravel quarry

- The proposed quarry will be operated by adopting effective environmental management plan for the sustainable environment.
- Utilizing optimum natural resources considering future generations.
- Restoration of mined out pit by developing greenbelt around the pit and along the benches and making the pit fit for rain water storage.
- Our EMC aware that the environment is not only for human being; it is also for all living things such as plants, animals, micro flora and fauna, aquatic organisms etc.

- To combat global warming, plantation of 500 saplings will be done in consultation with Forest Department.
- Create and maintain the safe workplaces for the workers to prevent occupational accidents.

1.10 Conclusion

As discussed, it is safe to say that the project is not likely to cause significant impact on the ecology and environment of the area, as adequate preventive measures will be adopted to contain the pollutants within permissible limits. The total operation shall be carried out with ease & minimum risk of the workers. The proposed Environmental Management Plan will keep the area in a safe environment with negligible impact on the environment. Plantation will substantiate the impact due to the mining activity. Mining activity will help in improving the socio–economic benefits in areas like employment, communication and infrastructure development etc.